

Unites many talents!

The IMG series

Model	Cutting width	Side shift (in cm)		Number of blades	Weight	Power requirement	Dimensions (closed swing arms)	
		Centre of tractor					Width	Depth
IMG 160/48	125 - 160 cm	63 62		2 + 1	355 kg	22 hp	130 cm	160 cm
		-7 132 (+36)						
IMG 175/58	125 - 175 cm	63 62		2 + 1	360 kg	24 hp	130 cm	170 cm
		-7 132 (+49)						
IMG 185/48	150 - 185 cm	76 74		2 + 1	385 kg	27 hp	155 cm	170 cm
		2 148 (+36)						
IMG 200/58	150 - 200 cm	76 74		2 + 1	390 kg	29 hp	155 cm	175 cm
		2 148 (+49)						



Wide offset!

Allows centralized tractor passage throughout the orchard. The grass discharge can be selected to be either to the center or underneath the trees.

Reliable technology!

Robust angular gears, indirect drive of the blades via V-belt and protective labyrinth seal of the blade bearings

Ideal ground hugging thanks to three-point suspension with integrated float position (Cat. I)

Intelligent, solid construction!

Compact, weight-optimized and extremely manoeuvrable thanks to the high tensile steels and quality components



That's fun!

Easy and quick maintenance thanks to directly accessible belt tensioners and lubrication points

All inclusive!
Front-rear mounting and hydraulic side shifting



Extreme blade overlap!

The extreme blade overlap guarantees optimum mulching results even under the most difficult conditions.



Snakes its way through!

No matter if spring loaded or with fine touch automation, the swing-arm snakes around any obstacle. Thanks to integrated weight relief the swing-arm disc glides gently over the ground.